

# MAX CCTV

## 260 INFRARED CAMERA

- 11 INFRARED LEDS ●
- 420-LINE RESOLUTION ●
- DUAL MOUNTING OPTIONS ●
- SMALL FORM FACTOR ●
- REMOVABLE SUN/LIGHT SHIELD ●
- AVAILABLE IN BLACK AND BEIGE ●



Radiant Infrared Source  
11 IR LEDs, photo-sensor controlled



Attached power and video cable



Removable sun/light shield



Includes adjustable metal bracket

### SPECIFICATIONS

|   |
|---|
| Horizontal resolution: 420 lines  |
| Effective pixels: NTSC - 512 x 492 (251k)<br>PAL - 512 x 582 (297k)                       |
| Video sensor: 1/4" CCD with digital signal processing (DSP)                               |
| Optics: 3.6mm coated precision fixed focus lens   |
| Sync.: Internal   |
| Scanning system: 2:1  |
| Minimum illumination: 0.8 LUX   |
| Signal-to-noise ratio: >48dB  |
| Gain control: Auto-gain control (AGC)   |
| White balance: Auto-white balance (AWB)   |
| Auto Electronic shutter: 1/60- to 1/10,000-second   |
| Infrared source: 11 units IR LEDs operating at 850nm                                      |
| Infrared switching: Automatic, photo-sensor control                                       |
| Power: 12VDC @ 150mA (nominal)  |
| Output: 1Vp-p composite video output @ 75 ohms  |
| Operating Temperature: -5°~50°C (23°~122°F)   |
| Housing: molded acrylic available in black and beige                                      |
| Bracket: metal ball-in-socket, 360° adjustable  |
| Dimensions: 1.75" wide x 2.13 tall (slightly less with light shield removed) x 3.75" long |

MYCCTVCAMERA.COM