



STI-PLEX4 4-CAMERA DVR



- MONITOR OVER THE INTERNET USING IE BROWSER ●
- ADVANCED H.264 COMPRESSION FORMAT ●
- 4 VIDEO INPUTS, 1 AUDIO INPUT ●
- INFRARED REMOTE CONTROL ●
- USB MOUSE SUPPORT ●

FEATURES

- Mobile Surveillance** - Smart phone support for mobile surveillance.
- Pentaplex Operation** - Multiple operations at once - live record, playback or backup, network operation, etc..
- Remote Surveillance** - Use Internet Explorer browser and client software. Functions include remote monitoring, remote playback, remote recording, and remote DVR control.
- Multiple Recording Modes** - Timer, motion triggered, and alarm triggered.
- Easy Network Connection** - RJ45-style connector on back panel supports multiple protocols TCP/IP, DHCP, DDNS, and PPPoE.
- A/V Support** - 1 (one) audio channel in, 1 (one) audio channel out (mono) over RCA connectors.
- Alarm/Sensor Support** - NO or NC support, 4 (four) inputs. 1 (one) output.
- PTZ Support** - Built-in RS485 connector for controlling pan/tilt/zoom camera.
- Search Modes** - Search recorded video using a variety of search criteria.
- Miscellaneous** - Pan/tilt/zoom support, RS485, USB mouse support, on-screen display menu, multiple display and record modes.

Storage & Hardware Specifications


HDD interface: SATA
External storage: external USB devices
USB Mouse Support
Network connection: LAN RJ45 on rear panel
Network protocols: TCP/IP, PPPOE, DHCP, DDNS
Compression: Standard H.264
Video format: NTSC/PAL
Video input: 4 BNC connectors
Video output: 1 BNC connector, composite 1Vp-p, 75 ohms
Audio input: 1 Channel (1 RCA connector)
Audio output: 1 RCA connector (mono)
Alarm input: 4 channels (NO or NC)
Alarm output: 1 channel for alarm or device
Communication port: 1 RS485
Pan/Tilt/Zoom Support: YES, including Preset and Autocruise
Power: 12VDC (included)
Operating Temperature: 10°~40°C (50°~104°F)

Video & On Screen Display (OSD) Specifications

Maximum Recording Rate: 30/120 Images per Second (NTSC), 25/100 Images per Second (PAL)
Recording Resolution: 720 x 480, 360 x 240 (NTSC), 704 x 576, 352 x 288 (PAL)
Display Frame Rate: 120 Images per Second (NTSC), 100 Images per Second (PAL)
Display Resolution: 120 Images per Second (NTSC), 100 Images per Second (PAL)
Remote Operation Software: Client software, IE browser (Windows 2000, XP, Vista compatible)
Recording Modes: Manual / Timer / Motion / Sensor
Operation Modes: Simplex/Triplex selectable - simultaneous monitor, record, playback
Video Display & Picture Control: Full Screen and Quad, with Multiple Quality Settings
Video Search Functions: Time, alarm event, motion detection event, list
Remote Menu Setup Support
Remote View: Supports Microsoft Internet Explorer Browser and client software
Event Log List Support
Supports Multi-level User Management, User Rights Authorized
Supports File Management, Delete or Lock Every Recording File Manually
Support Mobile Surveillance by Smart Phones
Users Manual and Infrared Remote Control Included



IR REMOTE CONTROL INCLUDED!



USB MOUSE SUPPORT!